

PressMax[®] 30ARS Fountain Additive

An Alcohol Substitute for Sheetfed Presses With Continuous Dampening System

PRODUCT DESCRIPTION

PressMax 30ARS Fountain Additive is a proven replacement for alcohol on sheetfed presses equipped with continuous dampening systems. It is recommended for Heidelberg Alcolor dampening systems. It is an effective companion for use with PressMax 20 Fountain Concentrate. This two-part fountain system replacing alcohol allows the pressman greater wetting control on press by varying the dosage of PressMax 30ARS.

FEATURES

- Effectively eliminates alcohol use on press.
- Minimizes dampening adjustments.
- Variable dosage provides wetting level control on press.
- Reduces VOC level compared to alcohol.
- Non-flammable.

INSTRUCTIONS FOR USE

To replace alcohol and achieve the desired level of wetting power, add 2 to 4 ounces of PressMax 30ARS Fountain Additive to the press-ready fountain solution. PressMax 30ARS will not alter conductivity readings. For optimum performance on press, the fountain solution circulator should be clean and the temperature set at 60°F ± 5.

TECHNICAL DATA

VOC	6.5 lbs./gallon
Glycol ether solvents	81.0%
Specific Gravity	0.92
Dosage	2 to 4 oz./gallon

PRESS-READY SOLUTION

Dilution	3 oz./gallon DI water
Conductivity	No change
Surface Tension	29-34 dynes/cm.

ORDERING INFORMATION

Catalog Number	Size
890128	4 x 1 gallon
890130	5 gallon pail
890129	30 gallon drum
890131	55 gallon drum

PM Fountain 04.03 Revised