

PressMax[®] 31ARS Fountain Additive

An Alcohol Substitute for Sheetfed Presses With Continuous Dampening System

PRODUCT DESCRIPTION

PressMax 31ARS Fountain Additive is a proven replacement for alcohol on sheetfed presses equipped with continuous dampening systems. This alcohol substitute product was specially formulated for use with the Dahlgren type dampening systems. PressMax 31ARS provides excellent through-put on this system.

FEATURES

- Effectively eliminates alcohol use on press.
- Minimizes dampening adjustments.
- Variable dosage provides wetting level control on press.
- Reduces VOC level compared to alcohol use.
- Non-flammable.

INSTRUCTIONS FOR USE

To replace alcohol and achieve the desired level of wetting power, add 2 to 4 ounces of PressMax 31ARS Fountain Additive to the press-ready fountain solution. PressMax 31ARS will not alter conductivity readings. For optimum performance on press, the fountain solution circulator should be clean and the temperature set at 60°F ± 5.

TECHNICAL DATA

VOC	6.64 lbs./gallon
Glycol ether solvents	54.0%
Specific Gravity	0.95
Dosage	2 to 4 oz./gallon

PRESS-READY SOLUTION

Dilution	3 oz./gallon DI water
Conductivity	No change
Surface Tension	32-36 dynes/cm.

ORDERING INFORMATION

Catalog Number	Size
890139	4 x 1 gallon
890132	5 gallon pail
890133	55 gallon drum

PM Fountain 04.03 Revised