



EC[®] Neg UNILEC[™] LR Fixer Replenisher (Electrolytic)

For Processing C-41 and Compatible Color Negative Films

Catalog Number: 600001026 (37.5 G)

DESCRIPTION

This product is a Process C-41 fixer designed for use in all processing equipment configured with continuously closed-looped electrolytic desilvering systems.

SAFE HANDLING INSTRUCTIONS

Please refer to Material Safety Data Sheets (MSDS) for specific chemical details. For emergencies, please contact CHEMTREC at 1-800-424-9300. You can obtain an MSDS by calling the Fujifilm Technical Hotline at 1-800-526-0851 Ext. 10.

HMS INFORMATION

Hazardous Materials Identification System. Please refer to Section 3 in the MSDS for further information.

	Concentrate	Replenisher	Working Tank
Health	1	1	1
Flammability	0	0	0
Reactivity	0	0	0
Personal Protection	C	C	C

SPECS & RECOMMENDATIONS

Temperature	35° – 41° C 95° – 105° F			
Processing Time	4'20" – 6'30"			
Starting Replenishment Rate (rate/roll)	135-24		APS-25	
	Cine	R & T	Cine	R & T
	10.5 ml	15 ml	7.4 ml	10.8 ml

SPECIFIC GRAVITY & pH

	pH @ 25° C	SpG @ 20° C	SpG @ 37.8° C
Replenisher Tank	8.50 ± 0.20	1.133 ± 0.003	1.126 ± 0.003
Fresh Tank	8.45 ± 0.15	1.100 ± 0.003	1.093 ± 0.003
Seasoned Tank #1	6.60 ± 0.40	1.120 ± 0.020*	1.113 ± 0.020*
Seasoned Tank #2	7.00 ± 0.50	1.120 ± 0.020**	1.113 ± 0.020**

* Silver concentration between 0.5 and 1.0 g/l

** Silver concentration between 0.2 and 0.8 g/l

MIXING INSTRUCTIONS – REPLENISHER

R	Water 95° – 105° F (35° – 41° C)	Concentrate
37.5 Gallons	22.5 G	15 G 1 Drum
1 Liter	600 ml	400 ml
1 Gallon	76.8 oz	51.2 oz

To Make 37.5 Gallons of Replenisher:

1. Start with 22.5 gallons of warm water.
2. Add 1 drum concentrate. Mix 3-5 minutes or until uniform.

RINSE DRUM BEFORE DISPOSAL

MIXING INSTRUCTIONS – WORKING TANK

W	Warm Water	Fixer Replenisher
1 Liter	250 ml	750 ml
1 Gallon	32 oz	96 oz
Tank Volume		
YOUR TANK		

To calculate the amount of water and fixer replenisher that you will need, multiply your tank volume by each of the numbers listed, in either liters or gallons. For example, if you have a 10 liter tank, 10x250 ml = 2.5 liters of water and 10x750 ml = 7.5 liters of fixer replenisher.

1000 ml = 1 liter 128 oz = 1 gallon

SHELF LIFE

	Concentrate	Replenisher	Working Tank
Time	U = 18 Months O = 8 Weeks	4 Weeks	1 Week
Color	Clear, Colorless	Clear, Colorless	Clear, Colorless
Odor	Slight Ammonia	Slight Ammonia	Slight Ammonia

U = Unopened, O = Opened

The data contained in this photographic bulletin is believed to be true and accurate, but is offered solely for your consideration, investigation, and verification. Nothing herein shall be construed to be a warranty or guarantee by either FUJI HUNT Chemicals, Inc. or any of its affiliates, and all such warranties, implied or otherwise, including any implied warranty of merchantability, are hereby expressly disclaimed. You, of course, are fully responsible for any use and / or domestic or foreign sale of the product(s) described, and nothing in this photographic bulletin shall be construed to constitute permission or a recommendation to practice any invention covered by patent or patent application or know-how owned by FUJIFILM, its affiliates, or others.

Bulletin Number: TB818718
Effective: January 2010
Replaces Bulletin Dated: February 2004

Fuji Hunt Chemicals, Inc.
40 Boroline Road
Allendale, New Jersey 07401

FUJIFILM

Technical Hotline
1-800-526-0851 Ext. 10